



FlashVent™ BREATHER VENT

Single Ply Low Slope Systems

OVERVIEW

FlashCo's One-Way and Two-Way Breather Vent helps deliver pressure equalization within the roofing assembly to reduce moisture and release trapped air. The One-Way vents allow trapped air pressure to escape, and Two-Way vents, in conjunction with the One-Way vents, help to reduce moisture by allowing air movement within the assembly.

For White TPO applications FlashCo pre-attaches a 60 mil reinforced membrane flange for easier welding during install. The base and cap are not only compounded for superior strength but also with a weathering package that is second to none. For all non-white TPO applications FlashCo prefabricates a boot that goes over the base prior to cap being attached. Therefore, if your field membrane is PVC or any color FlashCo has you covered. The cap however only comes in white and could be painted to match. This breather vent is the only single ply breather vent on the market that meets the standard 8" minimum height requirement.

Consult roofing system manufacturer for proper spacing requirements and where to locate the one-way versus the two-way as the vents work in conjunction with one another. Each breather vent is stamped with one-way or two-way so inspectors and others know what the vent is after it is installed.

FEATURES AND BENEFITS

- Available in TPO and PVC
- Only Breather Vent meeting 8" minimum height specification
- Pre-attached flange or boot makes heat welding easy
- Vandal Proof Cap
- One-Way or Two-Way stamped on every part
- All major brands and NDL certified

INSTALLATION

FlashVents shall be installed in accordance with the recommendations and specifications of the roofing material manufacturer or architect if NDL job.

1. Heat weld or adhere the base flange to the deck membrane.
2. For TPO applications apply cut edge sealant.

Sizing, Characteristics & Box Quantity

Size	Qty/Box	Box Size	Wgt/Box
4" Breather Vent	12	18"x18"x18"	10 lbs

Product & Material Info.

Description	Material	Thickness
Cap	Pre-molded TPO	-
Vent	Pre-molded TPO	-
Mem. Base Flange	TPO (Rein) white	60 mil
Mem. Boot	PVC (Rein) any color	60 mil
Mem. Boot	TPO (Rein) any color other than white	60 mil

* Injection grade TPO is compounded with a weathering package

Dimensions:

Height	9"
Diameter	4.25"
Flange	7.5"
Membrane Patch	12"

STAMP SYMBOLS

