

TPO FlashMembrane™

Unreinforced Flashing Roll



Description

FlashCo's Non-Reinforced membrane is a 55-mil thermoplastic polyolefin (TPO) based product available in standard rolls of 24" x 50'. The Non-Reinforced or detail membrane is also available in cut to size for details such as T-Joints, Corners, Pipe Flashings, and other details when the use of prefabricated accessories are not feasible or readily available. Standard colors are white, tan, and gray.

Intended Uses

Generally, the intended use is to offer the roofing contractor flexibility if field fabrication is a must and time is short. Detail membrane is much easier to work with than reinforced membrane due to its increased flexibility and weldability. Therefore, if you have to make up a detail in the field, this membrane is easier to work with.

Applications

TPO Single ply roofing systems. Details for field fabrication of penetrations and protrusions such as pipes, tubes, curbs, sealant pockets, scuppers, vents, drains, and other details.

Features and Benefits

- Superior weldability.
- Designed for ease of field fabrication and installation.
- Compatible with all major TPO membranes.
- When field fabrication cannot be avoided FlashMembrane™ is a must have.

Packaging

Rolls are packaged in a plastic bag. Keep bag sealed or tied when not in use. Membrane that has been exposed to the weather for approximately 7 days or longer must be cleaned with membrane cleaner prior to hot air welding.

Typical Properties and Characteristics

Material Type	Thickness	Color
Non-Reinforced Membrane	.055" (55 mil)	White, Gray, & Tan
Sheet Size	Weight	Quantity/Bag
24in. x 50ft. (100ft ²) 610mm x 15.24m (9.3m ²)	28lbs (12.7 kg)	1

Innovative Flashings Saving the Contractor Time Since 2000

866-323-5274 * 150 Todd Road, Suite 400 * Santa Rosa, CA 95407 * Fax: 707-824-5858 * FlashCoMfg.com

FlashCo® is a trademark of FlashCo Manufacturing, Inc. ©2017

