



OVERVIEW

FlashCo's T-Top Vents are prefabricated gravity allowing free flowing air to the vented area. T-Top can also be used as exhaust vents for non-heated air such as bathroom and kitchen and are not recommended for furnaces or driers. The T-Top vent is located on the roof deck or a sloped wall on the roof and easily installed by lifting up the membrane flange and fastening the sub base to the substrate. The membrane flange is then heat welded to the field membrane if TPO/PVC or adhered if EPDM and preventing water from infiltrating the roofing system.

FlashCo's commercial grade T-Top vents are constructed with a metal sub base, a reinforced membrane boot, and a Kynar painted metal hood or top. FlashCo's sub base measures 8" high, meeting the minimum height requirement for low slope systems. The prefabricated membrane boot is made to be compatible with the roofing system. T-Tops are designed with ends, sometimes called ears, to prevent wind driven rain from entering the structure. Wire mesh can be incorporated on top of the sub base to keep rodents and insects out for gravity venting applications.

FlashVent™ T-TOP VENT

Single Ply Low Slope Systems

FEATURES AND BENEFITS

- Installs in Minutes
- No Field Fabrication Required
- Stops Wind Driven Rain
- Compatible with Single Ply Membrane
- Fastens through Coated Metal Flange
- Great for Fan Exhaust or Gravity Venting

FlashVents shall be installed in accordance with the recommendations and specifications of the roofing material manufacturer or architect if NDJ job.

1. Secure vent sub base to roof deck over appropriate sized hole with proper fasteners.
2. Heat weld or adhere the base flange to the deck membrane.
3. For TPO applications apply cut edge sealant.

Sizing, Characteristics & Box Quantity

| Size | Size & Membrane | NFA |
|----------|-----------------|-----|
| STVT04 | 4" TPO | 14 |
| STVT06 | 6" TPO | 31 |
| STVT08 | 8" TPO | 53 |
| SPVT04 | 4" PVC | 14 |
| SPVT06 | 6" PVC | 31 |
| SPVT08 | 8" PVC | 53 |
| STVTB412 | 4x12 TPO Box | 48 |
| SPVTB412 | 4x12 PVC Box | 48 |

*Standard size in stock

Product & Material Info.

| Description | Material | Thickness |
|--------------|--------------|---------------|
| Sub Base | Galv. Steel | 26 ga./0.019" |
| Mem. Boot | TPO (Rein) | 60 mil |
| Mem. Boot | PVC (Rein) | 60 mil |
| Mem. Boot | EPDM (Rein) | 60 mil |
| Hood/Top | Kynar Steel | 26 ga./0.019" |
| Box Sub Base | Coated Metal | |